

ABUCompact GMC

A lightweight, versatile chain hoist

NEW PRODUCT


Now with double reeving for up to 200 kg



The ABUCompact GMC electric chain hoist is supplied complete with chain container, chain and ABUCommander pendant control and is ready for immediate installation.

ABUCompact GMC is the latest product in the ABUS GM range. This electric chain hoist, an innovative addition to our range, is suitable for any application with loads up to 100 kg or 200 kg. The special features of the ABUCompact GMC include lightweight design and connection using a normal 230 V power socket. This compact chain hoist is designed for a wide variety of applications inside buildings. And there is another special feature: the ABUCommander pendant control allows infinitely variable stepless control of the lifting speed.

Technical data at a glance		
Type	GMC 100.12	GMC 200.6
Reeving	single	double
Load capacity	100 kg	200 kg
Lifting speed	0.7 to 12 m/min	0.3 to 6 m/min
Hook paths	3 / 6 / 10 / 20 m	3 / 6 / 10 m
Total weight (3 m hook path)	10 kg	12 kg
Height C	300 mm	345 mm
Voltage	single-phase, 230 V AC (+5/-15 %)	
FEM group	1Am	
Duty cycle	50 % ED	
Switching cycles	300 cycles per hour	
Degree of protection	IP 21	



ORDER

by fax (+49) 22 61 37-180

ABUS Kransysteme GmbH
Sonnenweg 1
D-51647 Gummersbach

Our address:

Company: _____

Name: _____

Address: _____

Postcode/Place: _____

Phone: _____ Fax: _____

Business sector: _____

We hereby order the following products from ABUS Kransysteme GmbH

Hook path	3 m	6 m	10 m	20 m
GMC 100.12	<input type="text"/> *	<input type="text"/> *	<input type="text"/> *	<input type="text"/> *
GMC 200.6	<input type="text"/> *	<input type="text"/> *	<input type="text"/> *	—

Please enter the number of units required in the appropriate box.

* Prices on application

The ABUCompact GMC electric chain hoist is supplied ex works complete with chain container, chain and ABUCommander pendant control and is ready for immediate installation.

Delivery address (if different from above)

Date

Signature

