





Flange clamp




Support console



Roof stool fixing



Tie console for reinforced concrete beams



Dowel fixing



Embracing bracket



Tie console

## **HB** support fixings

Standardised and interchangeable fixing solutions for a variety of mounting applications on site.




Short suspension



Inclined suspension



Inclined stiffener




Normal suspension

V-suspension

## Suspensions

Variable suspension options offer the required flexibility for your mounting situation.





HB110 S





HB150 S



Compact and load-


optimised HB profile in steel and aluminium for easy handling of loads.

HB150 A

Profile



HB190 S



HB190 A



HB240 S




Electric chain hoist ABUCompact

High-performance electric chain hoists from the ABUCompact series lift your loads reliably and safely. Innovative trolleys ensure a smooth-running and noise-optimised performance.

## ABUS HB system - product range

Direction of movement	Туре	Configuration sketch	Load Capacity	Max. crane girder length
Linear transport	Monorail system		2.000 kg	-
For area coverage	Single girder crane EHB		500 kg	10,0 m
			800 kg	10,0 m
		1	1.000 kg	9,0 m
			1.250 kg	4,0 m
	Single girder crane EHB-X (stooled-up crane)		500 kg	8,0 m
		8	800 kg	8,0 m
			1.000 kg	7,3 m
	Double girder crane ZHB		500 kg	12,0 m
			800 kg	12,0 m
			1.000 kg	12,0 m
	Stooled-up double girder crane ZHB-X (stooled-up crane)		500 kg	8,0 m
			800 kg	8,0 m
			1.000 kg	8,0 m
	Double girder crane ZHB-I (running on I-beams)		500 kg	12,0 m
			800 kg	12,0 m
			1.000 kg	12,0 m
	Single girder crane EHB-I (running on I-beams)		500 kg	10,0 m
			800 kg	10,0 m
			1.000 kg	9,0 m
			1.250 kg	4,0 m



We would be pleased to attend site to view your application and offer advice as to how an HB system may assist. Please contact us at:

ABUS Kransysteme GmbH
P.O. Box 10 01 62 · D-51601 Gummersbach · Germany
Phone +49 2261 37-7202
e-mail: info@abuscranes.com
www.abuscranes.com

